



ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: **80-075-06**

Valid from: 2024 07 22
until: 2025 07 13

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Certificate holder: **ELSTA-MOSDORFER Ges.m.b.H.**
Bahnstraße 29
8430 Kaindorf / Sulm
Austria

Product: **Empty enclosures for low voltage switchgear and controlgear assemblies**

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the certificate holder holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s): **TGM-VA EE 36008A, TGM-VA EE 36008**

Österreichischer Verband für Elektrotechnik
Head of OVE Certification

T. Neumayer
Digitally signed by T. Neumayer
Email=t.neumayer@ove.at



Wien, 2024 07 22

Dipl.-Ing. T. Neumayer

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.



Manufacturer:

ELSTA-MOSDORFER Ges.m.b.H.
Bahnstraße 29
8430 Kaindorf / Sulm
Austria

Factory location(s):

ELSTA-MOSDORFER Ges.m.b.H.
Bahnstraße 29
8430 Kaindorf / Sulm
Austria

Elsta Mosdorfer Bosnia d.o.o.
Industrijska zona Ciljuge II
75270 Zivinice
Bosnia and Herzegovina

Tested and certified according to:

ÖVE/ÖNORM EN 62208:2012-07-01
ÖVE/ÖNORM EN 61439-3:2013-06-01 (cl. 10.2.6)
ÖVE/ÖNORM EN 61439-5:2015-11-01 (cl. 8.1.3, 8.1.4, 8.1.5, 8.1.101, 8.2, 10.2, 10.3, 10.13)

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Empty enclosures for low voltage switchgear and controlgear assemblies

Type designation:

Rating:

2...; 3...; 4...; 6...; 7...;
A3...; E3...; A4...; E4...; A5...; E5...; A6...; E6...
Rated insulation voltage AC 1000 V, DC 1500 V
IP44 or IP54; IK10
see typelist

Trademark:

ELSTA MOSDORFER

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

Type reference (1)	Type reference (2)	Dimensions WxHxD [mm]			Degree of protection	IK-Code	Rated insulation voltage	Permissible loads	
		Width	Hight	Depth				Housing	Width
250/320/150	KDK; KHAS; 250	250	320	150	IP44	IK10	AC 1000 V / DC 1500 V	200 N	5 N
265/385/130	KÜK; 265; HSK 265	265	385	130	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
320/320/160	320; A0/E0; A/EK 0; HSK 320	320	320	160	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
320/520/180	321; A1/E1; A/EK1; HSK321	320	520	180	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
330/440/130	VSK; 330	330	440	130	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
330/440/150	VSK; 330	330	440	150	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
410/610/165	410, Trenn-AK; A2/E2	410	610	165	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
440/330/130	VSK ESK0; 440	440	330	130	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
440/330/150	VSK; 440; HSK 440	440	330	150	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
450/450/130	VSTV 451	450	450	130	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
450/450/165	HASK 451	450	450	165	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
450/600/165	HASK 451/600	450	600	165	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
472/712/180	A3/E3 hoch; A/EK3; A/AK3	472	712	180	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
472/712/180	ESK 2, 472; "Krone"	472	712	180	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
600/450/130	VSTV 601	600	450	130	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
600/450/165	HASK 601	600	450	165	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
712/472/180	A3/E3 quer; A/AK3; A/EK3	712	472	180	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
712/472/180	ESK 2, 712; "Krone"	712	472	180	IP44	IK10	AC 1000 V / DC 1500 V	350 N	30 N
A3/1 650/250	A/AK 3/1	440	654	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A3/1 850/200	A/AK 3/1 850/200	440	836	200	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A3/1 850/250	A/AK 3/1	440	836	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A3/1 850/320	A/AK 3/1 T	440	836	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A3/1 1080/250	A/AK 3/1 1080/250	440	1065	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A3/1 1080/320	A/AK 3/1 TH	440	1065	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
E3/1 620/250	-	490	620	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E3/1 820/250	A/EK 3/1	490	820	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E3/1 820/320	A/EK 3/1 T	490	820	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

Type reference (1)	Type reference (2)	Dimensions WxHxD [mm]			Degree of protection	IK-Code	Rated insulation voltage	Permissible loads	
		Width	Hight	Depth				Housing	Width
E3/1 1050/200	A/EK 3/1 H 1050/200	490	1050	200	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E3/1 1050/250	A/EK 3/1 H 1050/250	490	1050	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E3/1 1050/320	A/EK 3/1 TH	490	1050	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
A4 850/320	A/AK 4	590	836	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A4 1080/320	A/AK 4H	590	1065	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A4 1350/250	-	590	1350	252	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
A4 1350/320	-	590	1350	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E4 820/250	A/EK 4 820/250	640	820	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E4 820/320	A/EK 4	640	820	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E4 1050/250	A/EK 4 1050/250	640	1050	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E4 1050/320	A/EK 4H	640	1050	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E4 1350/205	-	608	1332	207	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E4 1350/250	-	608	1332	252	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E4 1350/320	-	608	1332	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
A5 850/320	A/AK 5	785	836	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	100 N
A5 1080/320	A/AK 5H	785	1065	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	100 N
A5 1350/250	-	785	1350	252	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
A5 1350/320	-	785	1350	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E5 820/250	A/EK 5 820/250	835	820	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E5 820/320	A/EK 5	835	820	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E5 1050/250	A/EK 5 1050/250	835	1050	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E5 1050/320	A/EK 5H	835	1050	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E5 1350/205	-	803	1332	207	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E5 1350/250	-	803	1332	252	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E5 1350/320	-	803	1332	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
A6 850/320	A/AK 6	1115	836	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A6 1080/320	A/AK 6H	1115	1065	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	500 N	100 N
A6 1350/320	-	1115	1350	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.

Type reference (1)	Type reference (2)	Dimensions WxHxD [mm]			Degree of protection	IK-Code	Rated insulation voltage	Permissible loads	
		Width	Hight	Depth				Housing	Width
E6 820/250	–	1165	820	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E6 820/320	A/EK 6	1165	820	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E6 1050/250	–	1165	1050	250	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E6 1050/320	A/EK 6H	1165	1050	322	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1000 N	200 N
E6 1350/205	–	1133	1332	207	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E6 1350/250	–	1133	1332	252	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N
E6 1350/320	–	1133	1332	324	IP44, IP54*	IK10	AC 1000 V / DC 1500 V	1500 N	100 N

* Model with additional door seal

OVE Certification

Accredited by the Austrian National Accreditation Body as Certification Body for products within the scope as given in the official decree and published under <https://akkreditierung-austria.gv.at>.